

Bearing No.	Boundary dimensions(mm)				Basic load ratings(kN)		Limiting speed (rpm)		Weight
	尺寸				额定负荷		极限转速		重量
轴承尺寸	d	D	B	r <sub>smin</sub>	Dynamic Cr	Static Cor	Grease	Oil	kg
					动态	静态	脂	油	
1300	10	35	11	0.6	7.25	1.62	18,000	21,000	0.058
1301	12	37	12	1	9.45	2.16	16,000	18,000	0.066
1302	15	42	13	1	9.55	2.3	13,000	16,000	0.092
1303	17	47	14	1	12.5	3.2	12,000	14,000	0.128
1304	20	52	15	1.1	12.4	3.35	11,000	13,000	0.16
1304K	20	52	15	1.1	12.4	3.35	11,000	13,000	0.158
1305	25	62	17	1.1	18	5	9,100	11,000	0.255
1305K	25	62	17	1.1	18	5	9,100	11,000	0.251
1306	30	72	19	1.1	21.3	6.3	7,700	9,100	0.383
1306K	30	72	19	1.1	21.3	6.3	7,700	9,100	0.377
1307	35	80	21	1.5	25.1	7.85	6,800	8,000	0.5
1307K	35	80	21	1.5	25.1	7.85	6,800	8,000	0.492
1308	40	90	23	1.5	29.6	9.7	6,000	7,000	0.709
1308K	40	90	23	1.5	29.6	9.7	6,000	7,000	0.698
1309	45	100	25	1.5	38	12.7	5,400	6,300	0.953
1309K	45	100	25	1.5	38	12.7	5,400	6,300	0.938
1310	50	110	27	2	43.5	14.1	4,900	5,800	1.2
1310K	50	110	27	2	43.5	14.1	4,900	5,800	1.18
1311	55	120	29	2	51.5	17.9	4,500	5,200	1.58
1311K	55	120	29	2	51.5	17.9	4,500	5,200	1.56
1312	60	130	31	2.1	57	20.8	4,100	4,800	1.96
1312K	60	130	31	2.1	57	20.8	4,100	4,800	1.93
1313	65	140	33	2.1	62	22.9	3,800	4,500	2.42
1313K	65	140	33	2.1	62	22.9	3,800	4,500	2.38
1314	70	150	35	2.1	74.5	27.7	3,500	4,200	2.99
1315	75	160	37	2.1	79.5	30	3,300	3,900	3.55
1315K	75	160	37	2.1	79.5	30	3,300	3,900	3.5
1316	80	170	39	2.1	88.5	33	3,100	3,600	4.17
1316K	80	170	39	2.1	88.5	33	3,100	3,600	4.11
1317	85	180	41	3	97.5	38	2,900	3,400	4.96
1317K	85	180	41	3	97.5	38	2,900	3,400	4.89
1318	90	190	43	3	116	44.5	2,700	3,200	5.78
1318K	90	190	43	3	116	44.5	2,700	3,200	5.69
1319	95	200	45	3	132	51	2,600	3,000	6.69

<b>1319K</b>	95	200	45	3	132	51	2,600	3,000	6.59
<b>1320</b>	100	215	47	3	143	57.5	2,400	2,900	8.3
<b>1320K</b>	100	215	47	3	143	57.5	2,400	2,900	8.19
<b>1321</b>	105	225	49	3	156	64.5	2,300	2,700	10
<b>1322</b>	110	240	50	3	164	71.5	2,200	2,600	11.8
<b>1322K</b>	110	240	50	3	164	71.5	2,200	2,600	11.7