


Four-point Contact Ball Slewing Bearing Without Teeth



Bearing No.	INA No.	Rothe Erde No.	LYC No.	TG No.	Dimensions(mm)					Installation size(mm)					Structure size(mm)					Tooth parameter(mm)					Rated axial static load (kN)	Weight(kg)		
					Da	D	di	H	La	Li	n1	n2	φ1	φ2	D1	d	b	h	B	C	Di	Da	m	z			do	x
SR11/170						170	70	40	148	90	6	6	φ9	M8				5	35	35	121.5	118.5					140	5.4
SR10/179						234	124.5	25	214	144.5	24	19	φ11	φ11					25	25	180	178					220	7
SR15/179	VU 140179					234	124.5	35	214	144.5	12	12	11	11				5	30	30	178	180					200	7
SR15/179Y						234	124.5	35	214	144.5	24	20	φ11	φ11				5	30	30	180.5	177.5					350	14.34
SR20/300				E.318.22.00.D.1		300	138	46	270	170	6	6	φ13.5	φ13.5				5	41	41	220	218					420	16
SR20/220	VU 200220			E.318.22.00.D.1		302	138	46	270	170	10	10	18	18				5	41	41	219	221					435	18.5
SR20/220Y	VU200220			E.318.15.01.AA.LM		302	140	46	270	170	10	10	φ18	M16				5	41	41	223	221					350	18.55
SR20/312						312	145.14	50	270	175	14	16	M15.88	M15.88				6	44	44	220.86	224.15					300	6.3
SR15/200						240	160	38										5	33	33	201	199					520	15.8
SR20/260Y						329	190	45	305	215	16	16	φ14	φ14	328	192		1	44	44	261.5	258.5					480	16.2
SR20/257						329	190	45	305	215	16	16	φ14	φ14	328	192		1	44	44	258	256					280	16.3
SR20/326A						326	191	46	305	215	8	8	M8	M8				5	41	41	261	259					280	15.1
SR20/326						326	191	46	305	215	20	20	φ14	φ14				5	41	41	261	259					480	15
SR20/257A						329	191	45	305	215	20	20	φ14	φ14	327	193		4	41	41	258	256					420	14.8
SR20/260	VU.200.260			E.403.22.05.AA.LM		329	191	46	305	215	20	20	φ14	φ14		193		5	41	41	263	261					500	15
SR20/260Y1	VU 200260			E.403.22.01.CC.LM		326	191	46	305	215	20	20	14	14				5	41	41	259	261					540	18
SR20/260Y2				E.403.22.51.CC.LM		328	192	45	305	215	16	16	φ14	φ14	328	192			45	45	262	258					200	7.1
SR10/250				E.403.22.00.D1		300	200	35	280	220	16	16	M10	M10		200		5	30	30	251	249					830	49.6
SR30/435A						435	228	78	394.5	277	8	4	42006	42006				18	60	65	335	332					550	26.6
SR20/308						403.5	235	55	358	259	14	12	φ13	φ13	380			8	45	47	310.5	306.5					782	34.7
SR20/341			LY-Q020	E.403.22.00.D.1		440	240	55	400	280	18	18	M20-7H	22				5	50	50	342	340					820	32
SR25/345						430	260	65	400	290	24	24	φ14	φ16				12	53	53	348	342					460	12
SR 15/325	VU 140325					380	270	35	360	290	24	24	11	11				5	30	30	324	326					1010	45.4
SR25/485				E.403.22.00.D.1		485	275	55	453	307	8	8	M16	M16				5	50	50	382	378					1010	45.4
SR25/485Y						485	275	55	453	307	8	8	φ18	φ18				5	50	50	382	378					840	45
SR 25/380	VU 250380					485	275	55	453	307	16	16	18	18				5	50	50	379	381					872	43.7
SR20/383			LY-Q007			485	275	55	453	307	16	16	18	M16				5	50	50	386	381					872	43.7
SR20/383Y			LY-Q007K			485	275	55	453	307	16	16	18	18				5	50	50	386	381					470	17.3
SR17/402				E.535.25.00.D.1		402	278	44	383	298	12	12	φ9	M8				6	38	38	342	338					940	35
SR20/370		060.22.0370.301.11.1504				456	289	59	425	320	16	16	M16	M16				9	50	50	369	371						