



XU crossed roller slewing bearing



Identification number	Main dimensions								load rating	Tragfähigkeit		weight	
	inner ring d mm	outer ring D mm	Rollenteilkreisdurchmesser dp mm	width B mm	φLa	na	φLi	ni	□axial□	(radial)			
									Ca	C0a	Kr		Kor
									KN	KN	KN		KN
XU050077	40	112	77	22	97	6-φ6.6	56	6-M8	22.4	29	14.3	14.2	1.4
XU060094	57	140	94	26	120	6-φ9	70	6-M8	32.5	37.5	20.7	18.4	2.4
XU060111	76.2	145.79	111	15.87	133.1	8-φ6.9	88.9	8-φ6.9	36	44.5	22.8	21.5	1.2
XU080120	69	170	120	30	148	6-φ9	90	6-M8	56	53	35.5	26	4
XU080149	101.6	196.85	149.6	22.22	177.8	16-φ6.9	115.8	16-φ6.9	63	66	40	32.5	3.6
XU120179	124.5	234	179	35	214	12-φ11	144.5	12-φ11	118	179	75	88	7
XU120222	140	300	222	36	270	12-M16	170	12-φ18	133	275	85	131	12
XU160260	191	329	260	46	305	20-φ14	215	20-φ14	212	350	135	173	16
XU080264	215.9	311	264	25.4	295.3	12-φ8.7	231.8	12-φ8.7	85	117	54	57	6.9
XU160405	336	474	405	46	450	30-φ14	360	30-φ14	270	550	172	270	25
XU080430	380	480	430	26	462	20-φ9	398	20-M10	110	280	70	138	12
XU300515	384	646	515	86	598	18-φ26	432	18-φ26	720	1370	455	670	115