


Four point contact ball slewing bearing (with inner flange and external gear type)



Bearing		Rothe Erde Model	TG Model	Boundary dimensions (mm)				Bolt hole diameter (mm)				Structure dimensions (mm)														Gear Parameters (mm)				Basic load rating Coa (KN)	Weight (KG)
Model	INA Model			Da	D	di	H	La	Li	n1	n2	φ1	φ2	D1	d	b	h	B	C	Di	da	m	z	do	x						
SLOR20/414Y	VLA200414N ZT			503.3	304	56	455	332	10	12	M12	φ18	480	369.5	40	8.5	47.5	44.5	415.5	412.5	5	99	495		600	31.2					
SLOR20/414	VLA200414N			503.3	304	56	455	332	10	12	M12	18	480		40	11.5	47.5	44.5	415.5	412.5	5	99	495		295	29.5					
SLOR20/414Y1		231.20.0400.013		504	304	56	455	332	10	12	M12	18			45.5	10.5	45.5	45.5	415.5	412.5	5	99	495		250	29.3					
SLOR20/414Y2		231.20.0400.503		504	304	56	455	332	10	24	M12	18			45.5	10.5	45.5	45.5	415.5	412.5	5	99	495		250	29					
SLOR20/414			E.505.20.00.C	504	304	56	455	332	10	12	M12	φ18		375	46	10	46	46	415.5	412.5	5	99	495		500	33.3					
SLOR20/414A			E.505.20.C	504	304	56	455	332	10	12	M12	φ18		373	46	10	46	46	415.5	412.5	5	99	495		640	34					
SLOR20/505				505	304	56	455	332	10	12	M12	φ18		368	56	10	46	46	413	409	5	99	495		470	32					
SLOR20/414Y3		231.21.0475.013		504	305	56	455	332	10	12	M12	18			45.5	10.5	45.5	45.5	417	412.5	5	99	495		250	29.3					
SLOR20/544Y	VLA200544N ZT			640.3	434	56	585	462	14	14	M12	φ18		502	44.5	11.5	44.5	44.5	545.5	542.5	6	105	630		670	41.5					
SLOR20/544Y1	VLA200544N ZT			640.3	434	56	585	462	14	14	M12	φ18		499.5	44.5	8.5	47.5	44.5	545.5	542.5	6	105	630		790	41.6					
SLOR20/544Y4	VLA200544N			640.3	434	56	585	462	14	14	M12	18			44.5	11.5	47.5	44.5	545.5	542.5	6	105	630		385	41.5					
SLOR20/544Y3		231.20.0500.013		640.8	434	56	585	462	14	14	M12	18			45.5	10.5	45.5	45.5	545.5	542.5	6	105	630		330	39.5					
SLOR20/544Y5		231.20.0500.503		640.8	434	56	585	462	14	28	M12	18			45.5	10.5	45.5	45.5	545.5	542.5	6	105	630		330	39.2					
SLOR20/544			E.650.20.C	640.8	434	56	585	462	14	14	M12	φ18		505	46	10	46	46	545.5	542.5	6	105	630		670	40.6					
SLOR20/544B		231.20.0500.503		640.8	434	56	585	462	14	28	M12	φ18		505	45.5	10.5	45.5	45.5	545.5	542.5	6	105	630		660	40.6					
SLOR20/544Y2		231.21.0575.013		640.8	435	56	585	462	14	14	M12	18			45.5	10.5	45.5	45.5	547	542.5	6	105	630		330	39.5					
SLOR20/643				742	534	56	685	562	16	16	M12	φ18		598	46	10	46	46	645	641	6	122	732		740	51.4					
SLOR20/644Y	VLA200644N ZT			742.3	534	56	685	562	16	16	M12	φ18		599.5	44.5	8.5	47.5	44.5	645.5	642.5	6	122	732		900	50					
SLOR 20/644Y1	VLA 200644N			742.3	534	56	685	562	16	16	M12	18			44.5	11.5	47.5	44.5	645.5	642.5	6	122	732		455	48.5					
SLOR20/644Y2		231.20.0600.013		742.8	534	56	685	562	16	16	M12	18			45.5	10.5	45.5	45.5	645.5	642.5	6	122	732		390	47.6					
SLOR20/644Y3		231.20.0600.503		742.8	534	56	685	562	16	32	M12	18			45.5	10.5	45.5	45.5	645.5	642.5	6	122	732		390	47.2					
SLOR20/644			E.750.20.00.C	742.8	534	56	685	562	16	16	M12	φ18		605	46	10	46	46	645.5	642.5	6	122	732		780	55.1					
SLOR20/644Y4		231.21.0675.013		742.8	535	56	685	562	16	16	M12	18			45.5	10.5	45.5	45.5	647	642.5	6	122	732		390	47.6					
SBI-287				744	535	58	685	562	16	12	M12	M12		600	46	12	46	46	643	642	6	122	732		333	54.7					
SLOR20/744Y	VLA200744N ZT			838.1	634	56	785	662	18	16	M12	φ18		699.5	44.5	8.5	47.5	44.5	745.5	742.5	6	138	828		1050	56					
SLOR 20/744Y2	VLA 200744N			838.1	634	56	785	662	18	16	M12	18			44.5	11.5	47.5	44.5	745.5	742.5	6	138	828		530	54.5					
SLOR20/744Y3		231.20.0700.013		838.8	634	56	785	662	18	16	M12	18			45.5	10.5	45.5	45.5	745.5	742.5	6	138	828		450	53.5					
SLOR20/744Y1		231.20.0700.503		838.8	634	56	785	662	18	32	M12	18			45.5	10.5	45.5	45.5	745.5	742.5	6	138	828		450	53.1					
SLOR20/744			E.850.20.00.C	838.8	634	56	785	662	18	16	M12	φ18		705	46	10	46	46	745.5	742.5	6	138	828		910	60					
SLOR20/743				840	634	56	785	662	18	16	M12	φ18		698	46	10	46	46	745	741	6	138	828		840	57.7					